Safety Data Sheet

Issue Date: 01-Mar-2009 **Revision Date:** 24-Feb-2020 **Version** 2

1. IDENTIFICATION

Product identifier
Product Name NAPCO All Purpose Thinner

Other means of identification
SDS # NAP00012R

UN/ID No UN1263

Recommended use of the chemical and restrictions on use
Recommended Use Used for kitchen and bath refinishing.

Details of the supplier of the safety data sheet
Manufacturer Address
North America Polymer Company, Ltd.
7315 Hamlin Ave
Skokie, IL 60076 USA
Emergency telephone number
Company Phone Number 800-888-1081 / 847-779-6464
Emergency Telephone INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Clear liquid **Physical state** Liquid **Odor** Typical

Classification

The classification and labeling information in this Safety Data Sheet should be viewed as provisional, as physical test data has not been performed. This SDS was created using the criteria set forth by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) and is compliant with the Globally Harmonized System of Labeling and Classification of Chemicals (GHS).

Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 2

Signal Word
Danger

Hazard statements
Causes serious eye irritation
May cause drowsiness or dizziness
Highly flammable liquid and vapor

Precautionary Statements - Prevention
Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. — No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Use explosion-proof equipment
Keep cool

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a poison center or doctor/physician if you feel unwell
In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage
Store in a well-ventilated place. Keep container tightly closed
Store locked up

Precautionary Statements - Disposal
Dispose of contents/container to an approved waste disposal plant

Other hazards
Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
Methyl acetate	79-20-9	60-80
n-Butyl acetate	123-86-4	20-40

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General Advice Provide this SDS to medical personnel for treatment.

Eye Contact Immediately flush with plenty of water for up to 15 minutes. If eye irritation persists: Get medical advice/attention.

Skin Contact Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If skin irritation persists, call a physician.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If necessary, use artificial respiration to support vital functions. Call a poison center or doctor/physician if you feel unwell.

Ingestion Do NOT induce vomiting. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Immediate medical attention is required.

Most important symptoms and effects, both acute and delayed

Symptoms Causes serious eye irritation. May cause drowsiness or dizziness. Vapor causes irritation to nasal and respiratory passages. Will cause gastrointestinal tract irritation. Skin contact can lead to drying, defatting, itching, stinging and irritation.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media
Foam, Dry Chemical, Carbon Dioxide. If water is used, fog nozzles are preferable.

Unsuitable Extinguishing Media Water spray may be ineffective.

Specific Hazards Arising from the Chemical
Highly flammable liquid and vapor. Can form explosive mixtures at temperatures at or above flashpoint. Vapors may travel to source of ignition and flash back. Can form explosive mixtures at temperatures at or above the flashpoint. Material will float and may ignite on surface of water.

Hazardous combustion products Carbon oxides. Nitrogen oxides (NOx).

Explosion Data
Sensitivity to Static Discharge Flammable mixtures of this product are readily ignited even by static discharge.

Protective equipment and precautions for firefighters
As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions In case of a spill, clear the affected area and protect people. Eliminate all ignition sources. Use personal protection recommended in Section 8.

For Emergency Responders Full-body chemical protective clothing is recommended for emergency response procedures.

Environmental precautions

Environmental precautions Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See

Section 12, Ecological Information. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Soak up and contain spill with an inert (i.e. vermiculite, dry sand or earth) absorbent material.

Methods for Clean-Up Use non-sparking hand tools and explosion-proof electrical equipment. Sweep up and shovel into suitable containers for disposal. Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Avoid breathing dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Ground container and transfer equipment to eliminate static electric sparks. Use non-sparking hand tools and explosion-proof electrical equipment. Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing and eye/face protection. Potential peroxide former. If peroxide formation is suspected, do not open or move container. Always open containers slowly to allow any excess pressure to vent. After opening, purge container with nitrogen before reclosing. Wash face, hands and any exposed skin thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store in a well-ventilated place. Keep container tightly closed. Keep mixture in a cool, dry place away from everyone such as children, food, feed and domestic animals. Do not store in the trunks of autos. Keep away from incompatible materials, open flames, and high temperatures.

Incompatible Materials Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Methyl acetate 79-20-9	STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 610 mg/m^3 (vacated) TWA: 200 ppm (vacated) TWA: 610 mg/m^3 (vacated) STEL: 250 ppm (vacated) STEL: 760 mg/m^3	IDLH: 3100 ppm TWA: 200 ppm TWA: 610 mg/m^3 STEL: 250 ppm STEL: 760 mg/m^3
n-Butyl acetate 123-86-4	STEL: 150 ppm TWA: 50 ppm	TWA: 150 ppm TWA: 710 mg/m^3 (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m^3 (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m^3	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m^3 STEL: 200 ppm STEL: 950 mg/m^3

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits. Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS. For operations where contact can occur, a safety shower and an eye wash facility should be available.

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Splash goggles or safety glasses. Refer to 29 CFR 1910.133 for eye and face protection regulations.
Skin and Body Protection	Wear neoprene or butyl rubber gloves for routine industrial use. Use body protection appropriate for task. An apron or other impermeable body protection is suggested. Full-body chemical protective clothing is recommended for emergency response procedures. Refer to 29 CFR 1910.138 for appropriate skin and body protection.
Respiratory Protection	If respiratory protection is needed, use only protection authorized in the U.S. Federal OSHA Standard (29CFR 1910.134), applicable U.S. State regulations, or the Canadian CSA Standard Z94.4-93 and applicable standards of Canadian Provinces. Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmospheres, use of a full-facepiece pressure/demand SCBA or a full facepiece, supplied air respirator with auxiliary self-contained air supply is required under OSHA's Respiratory Protection Standard (1910.134-1998).
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid		
Appearance	Clear liquid	**Odor**	Typical
Color	Clear	**Odor Threshold**	Not determined

Property	**Values**	**Remarks • Method**
pH	Not determined	
Melting point / freezing point	Not determined	
Boiling point / boiling range	Not determined	
Flash point	Not determined	
Evaporation Rate	Not determined	
Flammability (Solid, Gas)	Not determined	
Flammability Limit in Air		
Upper flammability or explosive limits	Not determined	
Lower flammability or explosive limits	Not determined	
Vapor Pressure	Not determined	
Vapor Density	Not determined	
Relative Density	Not determined	
Water Solubility	Not determined	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Autoignition temperature	Not determined	
Decomposition temperature	Not determined	
Kinematic viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

10. STABILITY AND REACTIVITY

Reactivity
Not reactive under normal conditions.

Chemical stability
Stable under recommended storage conditions.

Possibility of hazardous reactions
None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid
Keep out of reach of children. Exposure to air. Keep away from heat, sparks, and open flame. Avoid impact, friction, and static electricity.

Incompatible materials
Strong oxidizing agents.

Hazardous decomposition products
Thermal decomposition may produce oxides of carbon.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Causes serious eye irritation.

Skin Contact Prolonged contact may cause redness and irritation.

Inhalation May cause drowsiness or dizziness. May cause irritation to the mucous membranes and upper respiratory tract.

Ingestion May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl acetate 79-20-9	> 5 g/kg (Rat)	> 5 g/kg (Rabbit)	> 49000 mg/m^3 (Rat) 4 h
n-Butyl acetate 123-86-4	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity Based on the information provided, this product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

STOT - single exposure May cause drowsiness or dizziness.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .
Oral LD50 6,158.60 mg/kg
Dermal LD50 6,678.40 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Methyl acetate 79-20-9	120: 72 h Desmodesmus subspicatus mg/L EC50	250 - 350: 96 h Brachydanio rerio mg/L LC50 static 295 - 348: 96 h Pimephales promelas mg/L LC50 flow-through	1026.7: 48 h Daphnia magna mg/L EC50
n-Butyl acetate 123-86-4	674.7: 72 h Desmodesmus subspicatus mg/L EC50	100: 96 h Lepomis macrochirus mg/L LC50 static 17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 62: 96 h Leuciscus idus mg/L LC50 static	72.8: 24 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Chemical name	Partition coefficient
Methyl acetate 79-20-9	0.18
n-Butyl acetate 123-86-4	1.81

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations. Since emptied containers retain product residue, follow label warnings even after container is emptied.

California Hazardous Waste Status

Chemical name	California Hazardous Waste Status
Methyl acetate 79-20-9	Toxic Ignitable
n-Butyl acetate 123-86-4	Toxic

14. TRANSPORT INFORMATION

Note Based on package size, product may be eligible for limited quantity exception.

DOT

UN/ID No UN1263

Proper Shipping Name Paint related material

Hazard class	3
Packing Group	II
Reportable Quantity (RQ)	5000lbs n-Butyl Acetate

IATA

UN number	UN1263
Proper Shipping Name	Paint related material
Transport hazard class(es)	3
Packing Group	II

IMDG

UN number	UN1263
Proper Shipping Name	Paint related material
Transport hazard class(es)	3
Packing Group	II

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	TSCA Inventory Status	DSL/NDSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Methyl acetate	X	ACTIVE	X	X	X	X	X	X	X
n-Butyl acetate	X	ACTIVE	X	X	X	X	X	X	X

Legend:

TSCA *- United States Toxic Substances Control Act Section 8(b) Inventory*

DSL/NDSL *- Canadian Domestic Substances List/Non-Domestic Substances List*

EINECS/ELINCS *- European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*

ENCS *- Japan Existing and New Chemical Substances*

IECSC *- China Inventory of Existing Chemical Substances*

KECL *- Korean Existing and Evaluated Chemical Substances*

PICCS *- Philippines Inventory of Chemicals and Chemical Substances*

AICS *- Australian Inventory of Chemical Substances*

US Federal Regulations

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
n-Butyl acetate 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

CWA (Clean Water Act)
This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
n-Butyl acetate	5000 lb			X

US State Regulations

California Proposition 65
This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Methyl acetate 79-20-9	X	X	X
n-Butyl acetate 123-86-4	X	X	X

16. OTHER INFORMATION

NFPA	**Health Hazards**	**Flammability**	**Instability**	**Special Hazards**
	Not determined	Not determined	Not determined	Not determined
HMIS	**Health Hazards**	**Flammability**	**Physical hazards**	**Personal Protection**
	2	3	0	X

Issue Date: 01-Mar-2009
Revision Date: 24-Feb-2020
Revision Note: New formula

Disclaimer
The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet