Safety Data Sheet

Issue Date: 12-Jun-2006 **Revision Date:** 06-Dec-2017 **Version** 2

1. IDENTIFICATION

Product Identifier

Product Name Overspray & Gun Cleaner

Other means of identification

SDS # NAP00017

UN/ID No UN1263

Recommended use of the chemical and restrictions on use

Recommended Use Used for kitchen and bath refinishing.

Details of the supplier of the safety data sheet

Manufacturer Address

North America Polymer Company, Ltd.
7315 Hamlin Ave
Skokie, IL 60076 USA

Emergency Telephone Number

Company Phone Number 800-888-1081 / 847-779-6464

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Clear liquid **Physical state** Liquid **Odor** Strong Organic

Classification

Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 1B
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Liquids	Category 3

Signal Word

Danger

Hazard statements

Harmful if swallowed
Causes skin irritation
Causes serious eye irritation
May cause cancer
Suspected of damaging fertility or the unborn child
May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways
Flammable liquid and vapor

Precautionary Statements - Prevention
Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Use only outdoors or in a well-ventilated area
Do not breathe dust/fume/gas/mist/vapors/spray
Keep away from heat/sparks/open flames/hot surfaces. — No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Use explosion-proof equipment
Keep cool

Precautionary Statements - Response
If exposed or concerned: Get medical advice/attention
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
If skin irritation occurs: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Rinse mouth
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting
In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage
Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal
Dispose of contents/container to an approved waste disposal plant

Other hazards
Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
Dichloromethane	75-09-2	60-70
Toluene	108-88-3	30-40

4. FIRST AID MEASURES

First Aid Measures

General Advice If exposed or concerned: Get medical advice/attention.

Eye Contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation occurs.

Skin Contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Get medical attention if irritation occurs.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician if you feel unwell.

Ingestion Do NOT induce vomiting. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Call a physician or poison control center immediately.

Most important symptoms and effects

Symptoms Causes eye irritation. Causes skin irritation. Prolonged breathing of vapors may cause nausea, headache, weakness and/or dizziness. Will cause gastrointestinal tract irritation. Harmful if swallowed.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Provide general supportive measures and treat symptomatically. Aggravates diseases of the blood, skin, eyes, liver, kidneys, lungs, cardiovascular, pulmonary and respiratory systems as well as alcoholism and rhythm disorders of the heart. Aspiration into the lungs may occur during ingestion or vomiting, causing lung damage or even death due to chemical pneumonia.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media
Dry chemical or CO2. Foam.

Unsuitable Extinguishing Media Water spray may be ineffective. If water is used, fog nozzles are preferable.

Specific Hazards Arising from the Chemical
Flammable liquid and vapor. Sealed containers may rupture when heated.

Hazardous Combustion Products Carbon oxides.

Explosion Data
Sensitivity to Static Discharge Flammable mixtures of this product are readily ignited even by static discharge.

Protective equipment and precautions for firefighters
As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions In case of a spill, clear the affected area and protect people. Wear protective clothing as described in Section 8 of this safety data sheet.

For Emergency Responders Remove all sources of ignition. Full-body chemical protective clothing is recommended for emergency response procedures.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment For small spills, absorb on polypads or other suitable non-reactive absorbent materials.

Methods for Clean-Up Eliminate all sources of ignition. Use non-sparking hand tools and explosion-proof electrical equipment. Sweep up and shovel into suitable containers for disposal. Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protection recommended in Section 8. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only in well-ventilated areas. Avoid breathing vapors or mists. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). All equipment used when handling the product must be grounded. Use non-sparking hand tools and explosion-proof electrical equipment. Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from heat, sparks, flame. Do not store in the trunks of autos. Keep locked up and out of reach of children.

Incompatible Materials Strong oxidizing agents. Acids. Bases. Alkali metals. Aluminum. Aluminum alloys. Zinc.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Dichloromethane 75-09-2	TWA: 50 ppm	TWA: 25 ppm (vacated) TWA: 500 ppm (vacated) STEL: 2000 ppm 5 min in any 3 h (vacated) Ceiling: 1000 ppm STEL: 125 ppm see 29 CFR 1910.1052	IDLH: 2300 ppm
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m^3 (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m^3 Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m^3 STEL: 150 ppm STEL: 560 mg/m^3

Appropriate engineering controls

Engineering Controls Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS. Eye wash fountain should be located in immediate work area.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Splash goggles or safety glasses. Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection Wear neoprene or butyl rubber gloves for routine industrial use. Use body protection appropriate for task. An apron or other impermeable body protection is suggested. Full-body chemical protective clothing is recommended for emergency response procedures. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection If respiratory protection is needed, use only protection authorized in the U.S. Federal OSHA Standard (29CFR 1910.134), applicable U.S. State regulations, or the Canadian CSA Standard Z94.4-93 and applicable standards of Canadian Provinces. Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmospheres, use of a full-facepiece pressure/demand SCBA or a full facepiece, supplied air respirator with auxiliary self-contained air supply is required under OSHA's Respiratory Protection Standard (1910.134-1998).

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid		
Appearance	Clear liquid	**Odor**	Strong Organic
Color	Clear	**Odor Threshold**	Not determined

Property	**Values**	**Remarks • Method**
pH	Not determined	
Melting Point/Freezing Point	Not determined	
Boiling Point/Boiling Range	40 °C / 104 °F	
Flash Point	30 °C / 85 °F	
Evaporation Rate	Not determined	
Flammability (Solid, Gas)	Not determined	
Flammability Limits in Air		
Upper Flammability Limits	Not determined	
Lower Flammability Limit	Not determined	
Vapor Pressure	Not determined	
Vapor Density	Not determined	
Relative Density	Not determined	
Water Solubility	Not determined	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Auto-ignition Temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

10. STABILITY AND REACTIVITY

Reactivity
Not reactive under normal conditions.

Chemical Stability
Stable under recommended storage conditions.

Possibility of Hazardous Reactions
None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid
Excessive heat, sparks and flames.

Incompatible Materials
Strong oxidizing agents. Acids. Bases. Alkali metals. Aluminum. Aluminum alloys. Zinc.

Hazardous Decomposition Products
Thermal decomposition may produce oxides of carbon.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Causes serious eye irritation.

Skin Contact Causes skin irritation.

Inhalation May cause drowsiness or dizziness. May cause irritation if inhaled.

Ingestion Harmful if swallowed. May be fatal if swallowed and enters airways.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Dichloromethane 75-09-2	= 1600 mg/kg (Rat)	-	= 53 mg/L (Rat) 6 h = 76000 mg/m^3 (Rat) 4 h
Toluene 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen. May cause cancer.

Chemical Name	ACGIH	IARC	NTP	OSHA
Dichloromethane 75-09-2	A3	Group 2A	Reasonably Anticipated	X
Toluene 108-88-3		Group 3		

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)
A3 - Animal Carcinogen
IARC (International Agency for Research on Cancer)
Group 2A - Probably Carcinogenic to Humans
Group 3 IARC components are "not classifiable as human carcinogens"
NTP (National Toxicology Program)
Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

Reproductive toxicity Suspected of damaging fertility or the unborn child.

STOT - single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 1,882.00 mg/kg
ATEmix (dermal) 12,000.00 mg/kg
ATEmix (inhalation-dust/mist) 12.50 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Dichloromethane 75-09-2	500: 72 h Pseudokirchneriella subcapitata mg/L EC50 500: 96 h Pseudokirchneriella subcapitata mg/L EC50	193: 96 h Lepomis macrochirus mg/L LC50 static 193: 96 h Lepomis macrochirus mg/L LC50 flow-through 262 - 855: 96 h Pimephales promelas mg/L LC50 static 140.8 - 277.8: 96 h Pimephales promelas mg/L LC50 flow-through	190: 48 h Daphnia magna mg/L EC50 1532 - 1847: 48 h Daphnia magna mg/L EC50 Static
Toluene 108-88-3	12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 433: 96 h Pseudokirchneriella subcapitata mg/L EC50	54: 96 h Oryzias latipes mg/L LC50 static 15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 12.6: 96 h Pimephales promelas mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50

Persistence/Degradability
Not determined.

Bioaccumulation
Not determined.

Mobility

Chemical Name	Partition Coefficient
Dichloromethane 75-09-2	1.25
Toluene 108-88-3	2.7

Other Adverse Effects
Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Dichloromethane 75-09-2	U080	Included in waste streams: F001, F002, F024, F025, F039, K009, K010, K156, K157, K158		U080
Toluene 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Dichloromethane 75-09-2	Category I - Volatiles		Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

Toluene 108-88-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Dichloromethane 75-09-2	Toxic
Toluene 108-88-3	Toxic Ignitable

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No	UN1263
Proper Shipping Name	Paint related material
Hazard Class	3
Packing Group	III
Special Provisions	Based on package size, product may be eligible for limited quantity exception

IATA

UN/ID No	UN1263
Proper Shipping Name	Paint related material
Hazard Class	3
Packing Group	III
Special Provisions	Based on package size, product may be eligible for limited quantity exception

IMDG

UN/ID No	UN1263
Proper Shipping Name	Paint related material
Hazard Class	3
Packing Group	III
Special Provisions	Based on package size, product may be eligible for limited quantity exception

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Dichloromethane	X	X	X	Present	X	Present	X	X
Toluene	X	X	X	Present	X	Present	X	X

Legend:

TSCA *- United States Toxic Substances Control Act Section 8(b) Inventory*

DSL/NDSL *- Canadian Domestic Substances List/Non-Domestic Substances List*

EINECS/ELINCS *- European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*

ENCS *- Japan Existing and New Chemical Substances*

IECSC *- China Inventory of Existing Chemical Substances*

KECL *- Korean Existing and Evaluated Chemical Substances*

PICCS *- Philippines Inventory of Chemicals and Chemical Substances*

AICS *- Australian Inventory of Chemical Substances*

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Dichloromethane 75-09-2	1000 lb 1 lb		RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
Toluene 108-88-3	1000 lb 1 lb		RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Dichloromethane - 75-09-2	75-09-2	60-70	0.1
Toluene - 108-88-3	108-88-3	30-40	1.0

CWA (Clean Water Act)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Dichloromethane		X	X	
Toluene	1000 lb	X	X	X

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Dichloromethane - 75-09-2	Carcinogen
Toluene - 108-88-3	Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Dichloromethane 75-09-2	X	X	X
Toluene 108-88-3	X	X	X

16. OTHER INFORMATION

NFPA	**Health Hazards**	**Flammability**	**Instability**	**Special Hazards**
	2	3	0	Not determined
HMIS	**Health Hazards**	**Flammability**	**Physical hazards**	**Personal Protection**
	Not determined	Not determined	Not determined	Not determined

Issue Date: 12-Jun-2006
Revision Date: 06-Dec-2017
Revision Note: Regulatory update Section 2 update

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet