



# Safety Data Sheet

Issue Date: 08-Oct-2015

Revision Date: 24-Nov-2017

Version 1

## 1. IDENTIFICATION

### Product Identifier

**Product Name** Regular Dry Poly-Glass Low Gloss White

### Other means of identification

**SDS #** NAP00031R

**UN/ID No** UN1263

### Recommended use of the chemical and restrictions on use

**Recommended Use** Used for kitchen and bath refinishing.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

North America Polymer Company, Ltd.  
7315 Hamlin Ave  
Skokie, IL 60076 USA

#### **Emergency Telephone Number**

**Company Phone Number** 800-888-1081 / 847-779-6464  
**Emergency Telephone (24 hr)** INFOTRAC 1-352-323-3500 (International)  
1-800-535-5053 (North America)

## 2. HAZARDS IDENTIFICATION

**Appearance** Liquid dispersion

**Physical state** Liquid

**Odor** Organic solvent

### Classification

The classification and labeling information in this Safety Data Sheet should be viewed as provisional, as the product's ingredients and percentages are kept as a trade secret / proprietary.

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable Liquids	Category 2

### Signal Word

**Danger**

### Hazard statements

Harmful if inhaled  
Causes skin irritation  
Suspected of causing cancer  
May cause drowsiness or dizziness  
May cause damage to organs through prolonged or repeated exposure  
Highly flammable liquid and vapor

**Precautionary Statements - Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Use only outdoors or in a well-ventilated area  
Wash face, hands and any exposed skin thoroughly after handling  
Wear eye/face protection  
Do not breathe dust/fume/gas/mist/vapors/spray  
Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Keep cool

**Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
If skin irritation occurs: Get medical advice/attention  
Wash contaminated clothing before reuse  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
Store in a well-ventilated place. Keep container tightly closed

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other hazards**

Toxic to aquatic life with long lasting effects

**Unknown Acute Toxicity**

NOTE: Acute Toxicity classifications / calculations are approximates

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
Titanium(IV) Oxide	13463-67-7	20-30
n-Butyl acetate	123-86-4	10-20
Methyl n-amyl ketone	110-43-0	10-20
Xylenes (o-, m-, p- isomers)	1330-20-7	5-10
n-Propyl acetate	109-60-4	1-5
Ethylbenzene	100-41-4	1-5

\*\*If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.\*\*

### 4. FIRST AID MEASURES

#### First Aid Measures

- Eye Contact** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- Skin Contact** Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
- Inhalation** IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention.
- Ingestion** If conscious give 2 glasses of water to dilute. Never give anything by mouth to a person who is unconscious or convulsing. Immediate medical attention is required.

**Self-Protection of the First Aider** Rescuers should put on appropriate protective gear.

#### Most important symptoms and effects

- Symptoms** May be harmful if swallowed. Causes eye irritation. Causes mild skin irritation. Direct eye contact may cause stinging, tearing and redness. May cause throat, esophagus and stomach irritation, nausea, vomiting, and diarrhea. Overexposure by inhalation may cause CNS depression- drowsiness, dizziness, confusion or loss of coordination. Loss of memory, anesthesia, unconsciousness and death. Contact with skin can cause irritation, (minor itching, burning an/or redness), dermatitis, defatting, may be readily absorbed through the skin.

#### Indication of any immediate medical attention and special treatment needed

- Notes to Physician** Overexposure to vapor, dust or mist may aggravate existing respiratory conditions, such as asthma, bronchitis, and inflammatory or fibrotic respiratory disease.

### 5. FIRE-FIGHTING MEASURES

#### Suitable Extinguishing Media

Foam, Dry Chemical, Carbon Dioxide.

**Unsuitable Extinguishing Media** Not determined.

#### Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor. Will be easily ignited by heat, sparks or flames. Solvent vapors are heavier than air and can travel along the ground and flashback.

**Hazardous Combustion Products** Oxides of carbon and nitrogen. Reactive hydrocarbons. Irritating vapors.

**Explosion Data**

**Sensitivity to Mechanical Impact** Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite/explode.

**Sensitivity to Static Discharge** Flammable mixtures of this product are readily ignited even by static discharge.

**Protective equipment and precautions for firefighters**

Water spray may be used for cooling containers to prevent possible pressure build-up and autoignition or explosion when exposed to extreme heat. In the event of fire, wear self-contained breathing apparatus. Avoid spreading burning liquid with water used for cooling.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal Precautions** Remove all sources of ignition. Avoid breathing vapors or mists. Ventilate affected area. Wear appropriate protective clothing and equipment to prevent contact. Take precautionary measures against static discharges.

**Environmental precautions**

**Environmental precautions** Prevent runoff from entering drains, sewers or streams. See Section 12 for additional Ecological Information.

**Methods and material for containment and cleaning up**

**Methods for Containment** Collect using an inert absorbent material and place in appropriate containers for disposal. For large spills: Flush spill area with water. Prevent runoff from entering drains, sewers, or streams.

**Methods for Clean-Up** Use non-sparking hand tools and explosion-proof electrical equipment. Sweep up and shovel into suitable containers for disposal. Dispose of contents/container to an approved waste disposal plant. For waste disposal, see section 13 of the SDS.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Advice on Safe Handling** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Use only outdoors or in a well-ventilated area. Wash face, hands and any exposed skin thoroughly after handling. Wear eye/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Ground/bond container and receiving equipment. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Keep cool.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Store locked up. Keep container tightly closed. Do not store at temperatures above 120°F. Keep away from heat, sparks, and flame. Store large quantities in buildings designed to comply with OSHA 1910.106. Keep containers closed when not in use and upright to prevent leakage. Store in a well-ventilated place. Keep cool.

**Incompatible Materials** Strong acids. Strong bases. Oxidizing agents.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Titanium(IV) Oxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
Methyl n-amyl ketone 110-43-0	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 465 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>
n-Butyl acetate 123-86-4	STEL: 150 ppm TWA: 50 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m <sup>3</sup> (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m <sup>3</sup>	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>
Xylenes (o-, m-, p- isomers) 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	-
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>
n-Propyl acetate 109-60-4	STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 840 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 840 mg/m <sup>3</sup> (vacated) STEL: 250 ppm (vacated) STEL: 1050 mg/m <sup>3</sup>	IDLH: 1700 ppm TWA: 200 ppm TWA: 840 mg/m <sup>3</sup> STEL: 250 ppm STEL: 1050 mg/m <sup>3</sup>

**Appropriate engineering controls**

**Engineering Controls**

Use local exhaust ventilation with a minimum capture velocity of 100 ft/min (0.5 m/sec) at the point of vapor evolution. Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the lower explosion limit and below current applicable exposure limits. Refer to OSHA 1910.94.

**Individual protection measures, such as personal protective equipment**

**Eye/Face Protection**

Splash goggles or safety glasses. Face Mask. Refer to 29 CFR 1910.133 for eye and face protection regulations.

**Skin and Body Protection**

Use solvent impermeable gloves to avoid contact with product. Wear suitable protective clothing. Wash contaminated clothing, including shoes, before reuse. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

**Respiratory Protection**

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**General Hygiene Considerations**

Handle in accordance with good industrial hygiene and safety practice. After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	Liquid	<b>Odor</b>	Organic solvent
<b>Appearance</b>	Liquid dispersion	<b>Odor Threshold</b>	Not determined
<b>Color</b>	Not determined		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>pH</b>	Not determined	
<b>Melting Point/Freezing Point</b>	Not determined	
<b>Boiling Point/Boiling Range</b>	101 °C / 213.8 °F	
<b>Flash Point</b>	18 °C / 64.4 °F	
<b>Evaporation Rate</b>	Not determined	
<b>Flammability (Solid, Gas)</b>	Not determined	
<b>Flammability Limits in Air</b>		
<b>Upper Flammability Limits</b>	Not determined	
<b>Lower Flammability Limit</b>	Not determined	
<b>Vapor Pressure</b>	Not determined	
<b>Vapor Density</b>	Not determined	
<b>Relative Density</b>	1.238	
<b>Water Solubility</b>	Not determined	
<b>Solubility in other solvents</b>	Not determined	
<b>Partition Coefficient</b>	Not determined	
<b>Auto-ignition Temperature</b>	Not determined	
<b>Decomposition Temperature</b>	Not determined	
<b>Kinematic Viscosity</b>	Not determined	
<b>Dynamic Viscosity</b>	Not determined	
<b>Explosive Properties</b>	Not determined	
<b>Oxidizing Properties</b>	Not determined	

### Other Information

**VOC Content (%)** 3.76 lb/gal

## 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions.

### Chemical Stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

**Hazardous Polymerization** Hazardous polymerization does not occur.

### Conditions to Avoid

Avoid all possible sources of ignition. Flammable vapors can be released at elevated temperatures.

### Incompatible Materials

Strong acids. Strong bases. Oxidizing agents.

### Hazardous Decomposition Products

Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>). Dense black smoke.

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

**Product Information**

- Eye Contact** Causes serious eye irritation.
- Skin Contact** Causes skin irritation.
- Inhalation** Harmful if inhaled. May cause drowsiness or dizziness.
- Ingestion** May be harmful if swallowed.

**Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium(IV) Oxide 13463-67-7	> 10000 mg/kg ( Rat )	-	-
Methyl n-amyl ketone 110-43-0	= 1600 mg/kg ( Rat ) = 1670 mg/kg ( Rat )	= 12600 µL/kg ( Rabbit ) = 12.6 mL/kg ( Rabbit )	> 2000 ppm ( Rat ) 4 h
n-Butyl acetate 123-86-4	= 10768 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	= 390 ppm ( Rat ) 4 h
Xylenes (o-, m-, p- isomers) 1330-20-7	= 3500 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit ) > 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.4 mg/L ( Rat ) 4 h
n-Propyl acetate 109-60-4	= 8700 mg/kg ( Rat )	> 17756 mg/kg ( Rabbit )	-
Water 7732-18-5	> 90 mL/kg ( Rat )	-	-

**Information on physical, chemical and toxicological effects**

- Symptoms** Causes eye irritation. Causes mild skin irritation. Direct eye contact may cause stinging, tearing and redness. May cause throat, esophagus and stomach irritation, nausea, vomiting, and diarrhea. Overexposure by inhalation may cause CNS depression-drowsiness, dizziness, confusion or loss of coordination. Loss of memory, anesthesia, unconsciousness and death. Contact with skin can cause irritation, (minor itching, burning an/or redness), dermatitis, defatting, may be readily absorbed through the skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

- Carcinogenicity** Suspected of causing cancer. Titanium dioxide is a possible carcinogen when it appears as a respirable dust.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium(IV) Oxide 13463-67-7		Group 2B		X
Xylenes (o-, m-, p- isomers) 1330-20-7		Group 3		
Ethylbenzene 100-41-4	A3	Group 2B		X

**Legend**

- ACGIH (American Conference of Governmental Industrial Hygienists)**
- A3 - Animal Carcinogen
- IARC (International Agency for Research on Cancer)**
- Group 2B - Possibly Carcinogenic to Humans
- Group 3 IARC components are "not classifiable as human carcinogens"
- OSHA (Occupational Safety and Health Administration of the US Department of Labor)**
- X - Present

**Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document .

**Unknown Acute Toxicity** NOTE: Acute Toxicity classifications / calculations are approximates.

ATEmix (oral) 2,011.00 mg/kg  
ATEmix (dermal) 5,232.00 mg/kg

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Toxic to aquatic life with long lasting effects.

**Component Information**

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Methyl n-amyI ketone 110-43-0		126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	
n-Butyl acetate 123-86-4	674.7: 72 h Desmodosmus subspicatus mg/L EC50	17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 62: 96 h Leuciscus idus mg/L LC50 static 100: 96 h Lepomis macrochirus mg/L LC50 static	72.8: 24 h Daphnia magna mg/L EC50
Xylenes (o-, m-, p- isomers) 1330-20-7		30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 13.4: 96 h Pimephales promelas mg/L LC50 flow-through 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50
Ethylbenzene 100-41-4	438: 96 h Pseudokirchneriella subcapitata mg/L EC50 4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	9.6: 96 h Poecilia reticulata mg/L LC50 static 11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
n-Propyl acetate 109-60-4		56 - 64: 96 h Pimephales promelas mg/L LC50 static 56 - 64: 96 h Pimephales promelas mg/L LC50 flow-through	318: 24 h Daphnia magna mg/L EC50

**Persistence/Degradability**

Not determined.

**Bioaccumulation**

Not determined.



**Mobility**

Chemical Name	Partition Coefficient
Methyl n-amyl ketone 110-43-0	1.98
n-Butyl acetate 123-86-4	1.81
Xylenes (o-, m-, p- isomers) 1330-20-7	2.77 - 3.15
Ethylbenzene 100-41-4	3.2

**Other Adverse Effects**

Not determined

**13. DISPOSAL CONSIDERATIONS****Waste Treatment Methods**

**Disposal of Wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated Packaging** Dispose of in accordance with federal, state and local regulations. Do not incinerate closed containers. Incinerate at an approved facility.

**US EPA Waste Number**

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylenes (o-, m-, p- isomers) 1330-20-7		Included in waste stream: F039		U239
Ethylbenzene 100-41-4		Included in waste stream: F039		

**California Hazardous Waste Status**

Chemical Name	California Hazardous Waste Status
n-Butyl acetate 123-86-4	Toxic
Xylenes (o-, m-, p- isomers) 1330-20-7	Toxic Ignitable
Ethylbenzene 100-41-4	Toxic Ignitable
n-Propyl acetate 109-60-4	Toxic Ignitable

**14. TRANSPORT INFORMATION****Note**

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

**DOT**

**UN/ID No** UN1263  
**Proper Shipping Name** Paint  
**Hazard Class** 3  
**Packing Group** II

**IATA**

**UN/ID No** UN1263  
**Proper Shipping Name** Paint  
**Hazard Class** 3  
**Packing Group** II

**IMDG**

<b>UN/ID No</b>	UN1263
<b>Proper Shipping Name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Marine Pollutant</b>	Yes

**15. REGULATORY INFORMATION**

**International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
Titanium(IV) Oxide	X	X	X	Present	X	Present	X	X
Methyl n-amyl ketone	X	X	X	Present	X	Present	X	X
n-Butyl acetate	X	X	X	Present	X	Present	X	X
Xylenes (o-, m-, p- isomers)	X	X	X	Present	X	Present	X	X
Ethylbenzene	X	X	X	Present	X	Present	X	X
n-Propyl acetate	X	X	X	Present	X	Present	X	X
Silica Gel	X	X		Present	X	Present	X	X
Water	X	X	X		X	Present	X	X

**Legend:**

- TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS** - Japan Existing and New Chemical Substances
- IECSC** - China Inventory of Existing Chemical Substances
- KECL** - Korean Existing and Evaluated Chemical Substances
- PICCS** - Philippines Inventory of Chemicals and Chemical Substances
- AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations**

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
n-Butyl acetate 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Xylenes (o-, m-, p- isomers) 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethylbenzene 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Xylenes (o-, m-, p- isomers) - 1330-20-7	1330-20-7	5-10	1.0
Ethylbenzene - 100-41-4	100-41-4	1-5	0.1

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
n-Butyl acetate	5000 lb			X
Xylenes (o-, m-, p- isomers)	100 lb			X
Ethylbenzene	1000 lb	X	X	X

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Titanium(IV) Oxide - 13463-67-7	Carcinogen
Ethylbenzene - 100-41-4	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Titanium(IV) Oxide 13463-67-7	X	X	X
Methyl n-amyl ketone 110-43-0	X	X	X
n-Butyl acetate 123-86-4	X	X	X
Xylenes (o-, m-, p- isomers) 1330-20-7	X	X	X
Ethylbenzene 100-41-4	X	X	X
n-Propyl acetate 109-60-4	X	X	X
Silica Gel 63231-67-4		X	X
Water 7732-18-5			X

**16. OTHER INFORMATION**

<b>NFPA</b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Instability</b>	<b>Special Hazards</b>
	Not determined	Not determined	Not determined	Not determined
<b>HMIS</b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Physical hazards</b>	<b>Personal Protection</b>
	2	3	0	H

Issue Date: 08-Oct-2015  
 Revision Date: 24-Nov-2017  
 Revision Note: Logo and Name Change

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet